

## 3a Double Rail Installation

Letters are drilled and tapped, mounted to two Aluminum C-Channel rails using stainless steel screws.

**Size:** 4" - 24" high letters

**Styles:** Any Style

**C-CHAN:** Max. 96" long - single piece

Letters are secured to rails (through backs) with stainless steel screws.

Letters are pre-attached to channels to insure proper hole location, then left either assembled (if smaller letters or short copy), or taken apart and shipped.

**Example**



**Sales: Enter using code: H3DRAIL**

### Feature Groups with Options

The following options must be reviewed with customers on Double Rail mounts.

#### Feature Group

##### **HDR-3 RAIL Finish**

(Rail finish options)

**Options:**

- |                          |              |
|--------------------------|--------------|
| <input type="checkbox"/> | ANODIZE RAIL |
| <input type="checkbox"/> | PAINT BLACK  |
| <input type="checkbox"/> | PAINT OTHER  |

##### **HDR-6 Punctuation Position**

(If copy has punctuation-choose option)

**Options:**

- |                          |                                 |
|--------------------------|---------------------------------|
| <input type="checkbox"/> | Punctuation attached to Letters |
| <input type="checkbox"/> | Punctuation attached to Rails   |
| <input type="checkbox"/> | NO Punctuation                  |

##### **HDR-4 RAIL Position**

(Position of letters to rail ends)

**Options:**

- |                          |   |
|--------------------------|---|
| <input type="checkbox"/> | Position letters FLUSH with Rails Ends. |
| <input type="checkbox"/> | EXTENDED rails beyond letter ends.      |

##### **HDR-7 Rail Length**

(Required rail lengths)

**Options:**

- |                          |                                |
|--------------------------|--------------------------------|
| <input type="checkbox"/> | Mount to rail by WORD.         |
| <input type="checkbox"/> | Use max. length rails possible |